

WP 1 SERIES

Area Wall Pack



ELECTRICAL STATS

SPECIFICATIONS	DETAILS			
WATTAGE	40W	60W	90W	120W
LUMENS	4000	6000	8410	12000
LUMENS/WATT	100 Lm/W			
COLOR	3000K, 4000K, 5000K			
INPUT VOLTAGE	100-277VAC			
DIMMABLE	Yes			
CRI	>70			
POWER FACTOR	>0.97 (120V) 0.92 (277V)			
WARRANTY	5 Years			
LENS	Shatter Proof Glass With Shield			
CERTIFICATIONS	DLC, ETL, FCC, CE, RoHS			
FINISH	Bronze			

Model	Dimensions	Weight	Replacement
40W	335 x 250 x 200mm (13.19" x 9.84" x 9.45")	5KGS (11 LBS)	175W MH
60W	425 x 250 x 240 (17.8" x 9.84" x 9.45")	7KGS (15.4 LBS)	250W MH
90W		8KGS (17.64 LBS)	400W MH
120W	365 x 235 x 190mm (14.38" x 9.23" x 7.5")	7KGS (15.4 LBS)	400W MH

DESCRIPTION

Our LED Wallpack is ideal for outdoor applications such as personnel doors, loading docks, and parking areas. The housing protects against moisture and other environmental conditions. The glass prismatic lens provides uniform light and is impact resistant/shatter proof.

FEATURES

- 40W, 60W, 90W, 120W
- 100-277VAC
- CRI>70
- 3000K, 4000K, 5000K
- Shatter Proof Glass
- 5 Year Warranty
- DLC, ETL, FCC, CE, RoHS
- Power Factor 0.97 (120V) 0.92 (277V)
- L70 - 50,000

ORDERING INFORMATION

SERIES		
WP1	-	XXX - XX
		40 = 40W 60 = 60W 90 = 90W 120 = 120W
		30 = 3000K 40 = 4000K 50 = 5000K