

SVT SERIES

Single Volumetric Troffer Series



ELECTRICAL STATS

SPECIFICATIONS	DETAILS		
WATTAGE	40W	50W	70W
LUMENS OUTPUT	4200Lm	5250Lm	7350Lm
COLOR TEMPERATURE	3000K, 4000K, 5000K		
INPUT VOLTAGE	100-277V		
CRI	>80		
POWER FACTOR	>0.9		
WARRANTY	5 Years		
SIZE	2 x 2ft	2 x 4ft	2 x 4ft
CERTIFICATIONS	UL, DLC		

DIMENSIONS	SIZE
2x2	603x603x107mm/23.74"x23.74"x4.21"
2x4	1213x603x107mm/47.75"x23.74"x4.21"

DESCRIPTION

The Single Volumetric Troffer is the designers choice in replacing traditional fluorescent troffers. Fast installation in T-bar grid drop-in ceilings.

Excellent color rendering and with it's anti glare lens, it makes an excellent choice for offices, schools, hospitals, and retail locations.

FEATURES

- 40W, 50W, 70W
- AC 100-277V
- 2x2 or 2x4
- UL, DLC
- Dimmable/Non Dimmable - 0-10V
- CRI 80
- L70 Rating 50,000 HRS L70
- 3000K, 4000K, 5000K

NOTES & PATENT INFORMATION

US Patent #7,307,391 8,115,411 8,791,650 9,179,513

Canada Patent #2,651,224 2,555,065 2,831,641

International Patents Pending

For complete and up to date patent information see our website

ORDERING INFORMATION

SERIES			
SVT	-	XX	- XX - X
40 = 2x2, 40W		30 = 3000K	D = Dimmable
50 = 2x4, 50W		40 = 4000K	N = Non-Dimmable
70 = 2x4, 70W		50 = 5000K	