

SP WALL PACK

Security Wall Pack



ELECTRICAL STATS

SPECIFICATION	DETAILS
WATTAGE	30W
LUMENS OUTPUT	2,500
POWER CONNECTION TYPE	HARDWIRE
CRI	>80
LIGHT OUTPUT ANGLE (BEAM)	120°
COLOR TEMPERATURES (CCT)	3000K, 4000K, 5000K
LUMEN MAINTENANCE	65,000 L70
INPUT VOLTAGE	100-277VAC
DIMMING	PHOTOCELL & MOTION SENSOR
POWER FACTOR	>0.92
THD	<20%
DIMENSIONS	11" x 6.8" x 5.35" (279 x 173 x 136mm)

DESCRIPTION

Our LED Security Wall Pack is ideal for applications by doorways, parkades, stairwells, and all other areas requiring extra illumination for security and safety purposes.

The casing protects against moisture and other enviromental conditions. The glass prismatic lens provides uniform light and impactresistant/shatter proof.

FEATURES

- 30W
- 100-277VAC
- Lumens
- 3000K, 4000K, 5000K
- CRI>80
- 5 Year Warranty
- ETL, FCC, CE, RoHS
- Shatter Proof Glass
- Bronze Finish
- Motion Sensor/ Photocell Optional

ORDERING INFORMATION

SERIES			
SP	-	30	- XX - XX
		30 = 30W	30=3000K 40=4000K 50=5000K
			M = Motion Sensor P = Photocell